Residential/Light Commercial Generator Accessories

KOHLER, Power Systems

Carburetor Heater Kits







GM19462-KP1-QS 6-14 kW Models GM57969-KP1-QS 17-20 kW Models

Applicable Models

- 6VSG
- 8.5RES
- 12RES
- 14RES/RESL/RESA/RESAL
- 17/18RES
- 20RES/RESL/RESA/RESAL

Description

The carburetor heater kit is recommended for improved cold starting in locations where the temperatures falls below 0° C (32° F). The carburetor heater prevents condensation and carburetor icing. The heater turns on when the temperature at the thermostat falls below approximately 4° C (40° F) and turns off when the temperature rises above approximately 16° C (60° F).

The carburetor heater for 6-14 kW models mounts between the engine air cleaner and the carburetor.

The carburetor heater for 17-20 kW models fits into a threaded opening on the carburetor, below the engine air cleaner.

Note: The heater requires a continuous source of power. Plug the carburetor heater into a 120 VAC receptacle provided on the generator set.

KOHLER CO., Kohler, Wisconsin 53044 USA Phone 920-457-4441, Fax 920-459-1646 For the nearest sales and service outlet in the US and Canada, phone 1-800-544-2444 KOHLERPower.com Kohler Power Systems Asia Pacific Headquarters 7 Jurong Pier Road Singapore 619159 Phone (65) 6264-6422, Fax (65) 6264-6455

Kit Contents

| Models | 6-14 kW | 17-20 kW | |
|---------------------------|----------------|----------------|--|
| Kits | GM19462-KP1-QS | GM57969-KP1-QS | |
| Description | Qty. | Qty. | |
| Bushing | 1 | 2 | |
| Cable tie | 2 | _ | |
| Decal | 1 | 1 | |
| Heater, carburetor | 1 | 1 | |
| Installation Instructions | 1 | 1 | |
| Insulator, breather line | 1 | _ | |
| Plug, button | 1 | _ | |
| Screw | 4 | _ | |
| Tube, breather | 1 | _ | |

Specifications

| Carburetor Heater Specifications | | | | | |
|----------------------------------|----------------------------------|-----------------|--|--|--|
| Kits | GM19462-KP1-QS | GM57969-KP1-QS | | | |
| Heater rating | 120 VAC, 37 W | | | | |
| Thermostat | 4°C/13°C (40°F/55°F) Snap action | | | | |
| Cord length | 1905 mm (75 in.) | 382 mm (15 in.) | | | |

| | | ED | |
|--|--|----|--|
| | | | |

Availability is subject to change without notice. Kohler Co. reserves the right to change the design or specifications without notice and without any obligation or liability whatsoever. Contact your local Kohler® generator distributor for availability.